

## IC 022, IC 022 PLUS

Discover a new dimension in surface cleaning with our revolutionary  
two - hose dry ice blasting system



**Standard dry ice pellets**  
1.5 mm / 3 mm



**Low air consumption**  
1,1 m³/min



**Lightweight**  
19 kg



**Low noise**  
65 - 85 dB (A)



**Added benefit**  
Maintenance free design

ERGONOMIC BLAST GUN  
WITH LED LIGHT

2 NOZZLES  
(ROUND & FLAT)

STANDARD AIR HOSE  
COUPLING

3 m BLAST  
HOSE

TROLLEY  
WITH STORAGE BOX

DRY ICE BOX  
25 KG



PRESSURE VALVE  
ON GUN



EASY - TO - OPERATE



ACCESSORIES



PATENTED FEEDING  
SYSTEM WITH GRINDER



Development



Manufacturing



Maintenance  
and Repair



Training

## Characteristics

Dry ice blasting has never been so affordable! Discover a new dimension of surface cleaning!

Dry ice cleaning is now also available to car workshops, car dealerships, all manufacturing or maintenance companies in any industry, big or small. We bring you a cost-effective alternative to traditional cleaning methods.

The unique design of the IC 022 offers surprising flexibility, performance and power. The maintenance-free feeding system from ICS accepts both 1,5 mm and standard 3 mm dry ice pellets.

The excellent design of the blaster allows easy handling even in tight access spaces. The operation of the machine is easy and fast to get used to.

With IC 022 you are equipped to manage very wide variety of cleaning tasks.

IC 022 with its unique feeding system offers unrivalled performance at an unbeatable price.

## Technical specifications

<ul style="list-style-type: none"><li>■ <b>Dimensions</b> <b>Length:</b> 528 mm <b>Width:</b> 296 mm <b>Height:</b> 336 mm</li></ul>	<ul style="list-style-type: none"><li>■ <b>Consumption</b> <b>Dry ice:</b> up to 24 kg/h <b>Compressed air:</b> 1,1 m<sup>3</sup>/min, depending on the nozzle type</li></ul>	<ul style="list-style-type: none"><li>■ <b>Input Pressure</b> up to 10 bars</li></ul>
<ul style="list-style-type: none"><li>■ <b>Weight</b> <b>Empty machine:</b> 19 kg with the hose</li></ul>	<ul style="list-style-type: none"><li>■ <b>Hopper capacity</b> 4 kg</li></ul>	<ul style="list-style-type: none"><li>■ <b>Operating pressure</b> 8 - 10 bars</li></ul>
<ul style="list-style-type: none"><li>■ <b>Material</b> <b>Casing:</b> Plastic <b>Wheel frame:</b> Stainless steel</li></ul>	<ul style="list-style-type: none"><li>■ <b>Noise level</b> 65 – 85 dB (A) depending on the blasting pressure and the cleaned surface</li></ul>	<ul style="list-style-type: none"><li>■ <b>Compressed air supply:</b> NW 7.2 coupling, acc. ISO 4414/EN 983 standard Minimum requirements for compressed air according to ISO 8573-1:2010 [1:4:1]</li></ul>

## HGS-N 5 Kompakt (10bar)

Oil-injected screw compressor suitable for IC 022 EVO



Air supply: 0.56 m<sup>3</sup>/min

- Mounted on 250 liter AD2000 recirculator
- Including refrigeration dryer with pre-filter and post-filter and automatic condensate drain
- Smartronic Lite control system
- IE3 drive motor with belt drive
- Smartrotor compressor
- Space-saving design
- Including cable and quick coupling




Development



Manufacturing



Maintenance  
and Repair



Training