

IC 110 E, IC 110 E PLUS

An electrical one-hose dry ice blasting machine
with very low compressed air demand



Standard dry ice pellets
1.5 mm / 3 mm



**Surprising performance
and low consumption**



**Easy
operation**



**Low
maintenance**



**Compact size
Mobile device**



REMOVABLE HANDLE

PLASTIC NOZZLE

ERGONOMIC BLAST GUN
WITH A SAFETY SWITCH

DIGITAL CONSUMPTION
INDICATOR

ANTI-VANDAL BUTTONS


17 KG INSULATED HOPPER

5 m BLAST HOSE 1/2"
WITH ANTI - KINK SPRING
HOSE GUARD

AUTOMATIC OIL-WATER
SEPARATOR

STAINLESS STEEL
HOUSING

GROUNDING KIT



PATENTED FEEDING SYSTEM



PRESSURE CONTROL,
DRY ICE CONSUMPTION CONTROL



ANTI - CLOGGING SYSTEM



STAINLESS STEEL QUICK CONNECT



Development



Manufacturing



Maintenance
and Repair



Training

Characteristics

IC 110 E is a medium ICS professional ice blaster designed for pressures of 10 bar or less which delivers exceptional cleaning performance while maintaining costs of the cleaning process at a minimum level.

The design predetermines this machine for businesses' in-house use for tool, machinery or mould maintenance applications.

The machine is characterised by unique compressed air consumption, starting at 0.5 m³/min, which makes the unit an unrivalled device in its class.

IC 110 E is a cost effective dry ice blasting solution suitable for variety of applications.

Technical specifications

- | | | |
|--|---|---|
| <ul style="list-style-type: none">■ Dimensions
Length: 597mm
Width: 446 mm
Height: 931 mm (incl. handle) | <ul style="list-style-type: none">■ Consumption
Dry ice: max. 60 kg/h
Compressed air: 0.5 – 4.5 m³/min.
(17,5-159 CFM) depending on the nozzle type | <ul style="list-style-type: none">■ Weight
Empty machine:
51 kg (without the hose) |
| <ul style="list-style-type: none">■ Operating pressure
max 10 bar / 145 PSI | <ul style="list-style-type: none">■ Hopper capacity
17 kg | <ul style="list-style-type: none">■ Material
Casing: stainless steel |
| <ul style="list-style-type: none">■ Service supply connections:
Compressed air : DIN 3489 claw coupling
Electrical: 100 – 240 V, 50 – 60 Hz | <ul style="list-style-type: none">■ Noise level
60 – 120 dB (A) depending on the blasting
pressure, nozzle type and the cleaned surface | |

IC 110 E



IC 110 E PLUS



Standard package contents

- | | |
|--|--|
| ■ Plastic nozzle RN-10-06
Round nozzle suitable for a wide range of uses | ■ Ergonomic Blast gun
With safety switch |
| ■ Blast hose
5 m 1/2" | |

PLUS Accesories

- | | |
|---|--|
| ■ Flat nozzle
FN-10-04-000 | ■ LED light for gun
IG-10-02-000 |
| ■ Compressed air hose
10 m 3/4" | ■ Ice shovel
2 kg Capacity |




Development



Manufacturing



Maintenance
and Repair



Training