

## Dry ice blasting machine IC 110-E

## Conversion kits

### Description of the machine

The electrically operated single-hose dry ice blasting machine impresses with the following benefits:

- very low air consumption
- 17 kg ice hopper
- continuously variable pellet regulation
- LED anti vandalism pushbuttons



### Roller

The Roller conversion kit consists of:

- 2 fixed and 2 steering castors with brake



### Desktop

The Desktop conversion kit consists of:

- 4 stainless steel feet with plastic cap



### Standard version

Dry ice blasting machine incl. 5 m hose package with blast gun IG 10-E, plastic round nozzle RN-10-05, grounding cable with rewinder, blast pressure regulation with pressure gauge, pellet regulation with digital ice consumption display, Trolley version with 2 solid wheels, mudguards, stainless steel supporting foot and stainless steel handle.

## Technical Parameters

Material of the machine:	<i>Case: Stainless steel</i>	
Dimensions:	Depth	597 mm
	Width	446 mm
	Height	931 mm
Empty weight:	49 kg (without hose package)	
Compressed air connection:	claw coupling, acc. DIN 3489	
Operating pressure:	max. 10 bar	
Hopper capacity:	17 kg	
Dry ice consumption:	1 - 60 kg/h	
Compressed air consumption:	0,3m <sup>3</sup> - 4,5 m <sup>3</sup> , depending on the nozzle combination	
Compressed air requirements:	clean, oil-free, dry, free of foreign bodies	
	<i>We recommend compressed air quality according ISO 8573-1:2010 [1:4:1]</i>	
Power connection:	100-240 V / 50-60Hz / 10 A CEE7/4 Typ F	
Noise level:	60 dB (A) - 120 dB (A) - depending on the nozzle combination and the surface of the object being cleaned	