

## Dry ice blasting machine IC 110

## Conversion kits

### Description of the machine

The pneumatically operated single-hose dry ice blasting machine impresses with the following benefits:

- low air consumption
- pellet regulation
- continuously variable blast pressure regulation



### Roller

The Roller conversion kit consists of:

- 2 fixed and 2 steering castors with brake



### Desktop

The Desktop conversion kit consists of:

- 4 stainless steel feet with plastic cap



### Standard version

Dry ice blasting machine incl. 5 m hose package with blast gun IG 10, plastic round nozzle RN-10-05, grounding cable with rewinder, blast pressure regulation with pressure gauge, pellet regulation with dry ice consumption display. Trolley version with 2 solid wheels, mudguards, stainless steel supporting foot and stainless steel handle.

## Technical Parameters

Material of the machine:	<i>Case: Stainless steel</i>
Dimensions:	<i>Length 597 mm</i> <i>Width 446 mm</i> <i>Height 931 mm</i>
Empty weight:	<i>39 kg (without hose package)</i>
Compressed air connection:	<i>claw coupling, acc. DIN 3489</i>
Operating pressure:	<i>max. 10 bar</i>
Hopper capacity:	<i>10 kg</i>
Dry ice consumption:	<i>5-45 kg/h</i>
Compressed air consumption:	<i>1,0 m<sup>3</sup> - 4,5 m<sup>3</sup>, depending on the nozzle combination</i>
Compressed air requirements:	<i>clean, oil free, dry, free of foreign bodies</i> <i>We recommend compressed air quality according ISO 8573-1:2010 [1:4:1]</i>
Noise Level:	<i>60 dB (A) - 120 dB (A) - depending on the nozzle combination and the surface of the object being cleaned</i>